

#### **SAFETY DATA SHEET**

# 2-Propanol

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE **COMPANY/UNDERTAKING**

#### **Product identifier** 1.1.

Trade name: 2-Propanol Product no.:

Other means of identification: Index No.: 603-117-00-0

> EC No.: 200-661-7 CAS No.: 67-63-0

IEX34

#### Relevant identified uses of the substance or mixture and uses advised against 1.2.

Relevant identified uses of the substance or mixture: Laboratory use Uses advised against: None known.

#### 1.3. Details of the supplier of the safety data sheet

Company and address: Laboratoriumdiscounter

> Zandvoortstraat 75 1976BN Ijmuiden Netherlands

Tel: +31 255 700 210

www.laboratoriumdiscounter.nl/en/ info@laboratoriumdiscounter.nl

Revision: 13/02/2023

SDS Version: 1.0

#### 1.4. **Emergency telephone number**

Contact The National Poisons Information Service (dial 111, 24 h service). See section 4 "First aid measures".

# **SECTION 2: HAZARDS IDENTIFICATION**

#### 2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour. Eye Irrit. 2; H319, Causes serious eye irritation. STOT SE 3; H336, May cause drowsiness or dizziness.

#### 2.2. Label elements

E-mail:

Hazard pictogram(s):



Signal word:

Hazard statement(s): Highly flammable liquid and vapour. (H225)

Causes serious eye irritation. (H319)

May cause drowsiness or dizziness. (H336)

2-Propanol Page 1 of 13



Safety statement(s):

General: If medical advice is needed, have product

container or label at hand. (P101) Keep out of reach of children. (P102)

Prevention: Wash hands thoroughly after handling.

(P264)

Wear eye protection/protective gloves/protective clothing. (P280)

Response: IF IN EYES: Rinse cautiously with water for

several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(P305+P351+P338)

If eye irritation persists: Get medical

advice/attention. (P337+P313)

Storage: Store in a well-ventilated place. Keep cool.

(P403+P235)

Disposal: Dispose of contents/container in accordance

with local regulation. (P501)

Hazardous substances: propan-2-ol;isopropyl alcohol;isopropanol

Additional labelling: Not applicable.

2.3. Other hazards

Additional warnings:

The material contains peroxide forming

substances, which can form hazardous levels

of peroxides e.g. during distillation,

evaporation or extraction.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

This product does not contain any

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605.

### **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

#### 3.1. Substances

Product/substance	Identifiers	% w/w	Classification	Note
propan-2-ol;isopropyl alcohol;isopropanol	CAS No.: 67-63-0 EC No.: 200-661-7 UK-REACH:	95-100%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
	Index No.: 603-117-00-0		3.3.323,11330	

# 3.2. Mixtures

Not applicable. This product is a substance.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

2-Propanol Page 2 of 13



#### Other information

-

### **SECTION 4: FIRST AID MEASURES**

# 4.1. Description of first aid measures

General information: In the case of accident: Contact a doctor or

casualty department – take the label or this

safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or

other drink.

Inhalation: Upon breathing difficulties or irritation of the

respiratory tract: Bring the person into fresh

air and stay with him/her.

Skin contact: Upon irritation: rinse with water. In the event

of continued irritation, seek medical

assistance.

Eye contact: Upon irritation of the eye: Remove contact

lenses. Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

*Ingestion:* If the person is conscious, rinse the mouth

with water and stay with the person. Never

give the person anything to drink.
In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking

on vomited material.

Burns: Rinse with water until pain stops then

continue to rinse for 30 minutes.

### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

# 4.3. Indication of any immediate medical attention and special treatment needed

2-Propanol Page 3 of 13

If eye irritation persists: Get medical advice/attention.

*Information to medics:* 

Bring this safety data sheet or the label from this product.

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

# 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: ●2YE

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

# 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid inhalation of vapours from spilled material.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

# 6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

# **SECTION 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

2-Propanol Page 4 of 13



The product should be tested for peroxides before distillation or evaporation and tested for peroxide formation or discarded after 1 year.

Peroxide formation may be present anywhere in the container, including the sides, bottom, exterior and threaded cap. Peroxide formation in ppm concentrations may not be visually observable and must be identified through the use of appropriate testing procedures. If any of the following conditions exist, the material may be explosively unstable and will require stabilization prior to use:

- 1. Material appears to be degraded and or contaminated.
- 2. Material appears to be discolored.
- 3. Deterioration or distortion of storage container.
- 4. Thermal shock (sunlight).
- 5. Age of material exceeds recommended storage time.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

# 7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed containers and store protected from moisture and light. Containers should be dated when opened and tested periodically for the presence of peroxides. Do not exceed storage time limits.

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Keep only in original packaging.

Storage temperature: Room temperature 15 to 25°C

*Incompatible materials:* Strong acids, strong bases, strong oxidizing

agents, and strong reducing agents.

#### 7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

### **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1. Control parameters

propan-2-ol;isopropyl alcohol;isopropanol Long term exposure limit (8 hours) (ppm): 400 Long term exposure limit (8 hours) (mg/m³): 999 Short term exposure limit (15 minutes) (ppm): 500 Short term exposure limit (15 minutes) (mg/m³): 1250

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.

EH40/2005 Workplace exposure limits (Fourth Edition 2020).

#### **DNEL**

propan-2-ol;isopropyl alcohol;isopropanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population		319 mg/kg bw/day
Long term – Systemic effects - Workers		888 mg/kg bw/day

2-Propanol Page 5 of 13

Long term – Systemic effects - General population	Inhalation	89 mg/m³
Long term – Systemic effects - Workers	Inhalation	500 mg/m³
Short term – Systemic effects - General population	Inhalation	178 mg/m³
Short term – Systemic effects - Workers	Inhalation	1000 mg/m <sup>3</sup>
Long term – Systemic effects - General population	Oral	26 mg/kg bw/day
Short term – Systemic effects - General population	Oral	51 mg/kg bw/day

#### **PNEC**

propan-2-ol;isopropyl alcohol;isopropanol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		140.9 mg/L
Freshwater sediment		552 mg/kg
Intermittent release (freshwater)		140.9 mg/L
Marine water		140.9 mg/L
Marine water sediment		552 mg/kg
Predators		160 mg/kg
Sewage treatment plant		2.251 g/L
Soil		28 mg/kg

# 8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Professional users are subjected to the

legally set maximum concentrations for occupational exposure. See occupational

hygiene limit values above.

Appropriate technical measures: The formation of vapours must be kept at a

minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures: In between use of the product and at the end

of the working day all exposed areas of the body must be washed thoroughly. Always

wash hands, forearms and face.

Measures to avoid environmental exposure: No specific requirements.

### 8.3. Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:

2-Propanol Page 6 of 13



Туре	Class	Colour	Standards	
	Class 2 (medium capacity)	Brown	EN14387	(B)

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0.4	> 480	EN374-2, EN374-3, EN388	

Eye protection:

Туре	Standards	
Safety glasses with side shields.	EN166	

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

# 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: Colourless

Odour / Odour threshold: Alcohol odor (Odour treshold: 1 - 196 ppm)

pH: Testing not relevant or not possible due to

the nature of the product.

*Density (g/cm³):* 0,79 g /cm³ bij 20 °C

Kinematic viscosity: Testing not relevant or not possible due to

the nature of the product.

Particle characteristics: Does not apply to liquids.

**Phase changes** 

*Melting point/Freezing point (°C):* -89

Softening point/range (waxes and pastes) (°C): Does not apply to liquids.

Boiling point (°C): 82

Vapour pressure: 43 hPa bij 20 °C

Relative vapour density: Testing not relevant or not possible due to

the nature of the product.

Decomposition temperature (°C): Not applicable

### Data on fire and explosion hazards

2-Propanol Page 7 of 13



Flash point (°C):

Flammability (°C): flammable liquid according to GHS criteria

*Auto-ignition temperature (°C):* 425 °C (DIN 51794)

Lower and upper explosion limit (% v/v): Testing not relevant or not possible due to

the nature of the product.

Solubility

Solubility in water: Testing not relevant or not possible due to

the nature of the product.

*n-octanol/water coefficient:* Testing not relevant or not possible due to

the nature of the product.

Solubility in fat (g/L): Testing not relevant or not possible due to

the nature of the product.

9.2. Other information

Other physical and chemical parameters: No data available.

# **SECTION 10: STABILITY AND REACTIVITY**

#### 10.1. Reactivity

No data available.

# 10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

# 10.3. Possibility of hazardous reactions

None known.

#### 10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure. Risk of formation of explosive peroxides when distilled, evaporated or otherwise concentrated.

### 10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

### 10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

### **SECTION 11: TOXICOLOGICAL INFORMATION**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

#### **Acute toxicity**

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

Based on available data, the classification criteria are not met.

#### Serious eye damage/irritation

Causes serious eye irritation.

# **Respiratory sensitisation**

Based on available data, the classification criteria are not met.

2-Propanol Page 8 of 13



#### Skin sensitisation

Based on available data, the classification criteria are not met.

# Germ cell mutagenicity

Based on available data, the classification criteria are not met.

# Carcinogenicity

Based on available data, the classification criteria are not met.

# Reproductive toxicity

Based on available data, the classification criteria are not met.

# **STOT-single exposure**

May cause drowsiness or dizziness.

# STOT-repeated exposure

Based on available data, the classification criteria are not met.

### **Aspiration hazard**

Based on available data, the classification criteria are not met.

#### 11.2. Information on other hazards

# Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

### **Endocrine disrupting properties**

None known.

#### Other information

propan-2-ol;isopropyl alcohol;isopropanol has been classified by IARC as a group 3 carcinogen.

# **SECTION 12: ECOLOGICAL INFORMATION**

# 12.1. Toxicity

No data available.

#### 12.2. Persistence and degradability

No data available.

#### 12.3. Bioaccumulative potential

No data available.

#### 12.4. Mobility in soil

No data available.

#### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Endocrine disrupting properties

None known.

# 12.7. Other adverse effects

2-Propanol Page 9 of 13



None known.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Product is covered by the regulations on hazardous waste.

To the extent the material has not been subject to regular tests of peroxide formation the waste shall be treated as explosive waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

### **EWC** code

Not applicable.

# Specific labelling

Not applicable.

# **Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

### **SECTION 14: TRANSPORT INFORMATION**

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Class: 3 Labels: 3 Classification code: F1	II		Limited quantities: 1 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Class: 3 Labels: 3 Classification code: F1	II		Limited quantities: 1 L EmS: F-E S-D See below for additional information.
IATA	UN1219	ISOPROPANOL (ISOPROPYL ALCOHOL)	Class: 3 Labels: 3 Classification code: F1	II	No	See below for additional information.

<sup>\*</sup> Packing group

2-Propanol Page 10 of 13

<sup>\*\*</sup> Environmental hazards

#### **Additional information**

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: ●2YE

# 14.6. Special precautions for user

Not applicable.

# 14.7. Maritime transport in bulk according to IMO instruments

No data available.

# **SECTION 15: REGULATORY INFORMATION**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: People under the age of 18 shall not be

exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate

exposure, must be considered.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances: P5c - FLAMMABLE LIQUIDS, Qualifying

quantity (lower-tier): 5.000 tonnes / (upper-

tier): 50.000 tonnes

Additional information: Tactile warning.

Sources: The Health and Safety at Work etc. Act 1974

Regulations 2013.

Control of Major Accident Hazards (COMAH)

Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and

amended in UK law.

Regulation (EC) No 1272/2008 on

classification, labelling and packaging of substances and mixtures (CLP) as retained

and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained

and amended in UK law.

# 15.2. Chemical safety assessment

No

2-Propanol Page 11 of 13



# **SECTION 16: OTHER INFORMATION**

# Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

H336, May cause drowsiness or dizziness.

# **Abbreviations and acronyms**

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

**UN = United Nations** 

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

#### Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental

2-Propanol Page 12 of 13



data.

# The safety data sheet is validated by

Laboratoriumdiscounter

#### Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products. It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en