

SAFETY DATA SHEET

Toluene 99.9 +%, extra pure

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Trade name: Toluene 99.9 +%, extra pure

Product no.: SMLPP

Other means of identification: Index No.: 601-021-00-3

EC No.: 203-625-9 CAS No.: 108-88-3

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture: Laboratory use Uses advised against: None known.

1.3. Details of the supplier of the safety data sheet

Company and address: Laboratorium discounter

Zandvoortstraat 75 1976BN Ijmuiden Netherlands

Tel: +31 255 700 210

www.laboratoriumdiscounter.nl/en/info@laboratoriumdiscounter.nl

Revision: 23/02/2023

SDS Version: 1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Flam. Liq. 2; H225, Highly flammable liquid and vapour.

Asp. Tox. 1; H304, May be fatal if swallowed and enters airways.

Skin Irrit. 2; H315, Causes skin irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

Repr. 2; H361, Suspected of damaging fertility or the unborn child.

STOT RE 2; H373, May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

E-mail:

Hazard pictogram(s):



Signal word: Danger

Toluene 99.9 +%, extra pure Page 1 of 12



Hazard statement(s): Highly flammable liquid and vapour. (H225)

May be fatal if swallowed and enters airways.

(H304)

Causes skin irritation. (H315)

May cause drowsiness or dizziness. (H336) Suspected of damaging fertility or the

unborn child. (H361)

May cause damage to organs through prolonged or repeated exposure. (H373)

Safety statement(s):

General: If medical advice is needed, have product

container or label at hand. (P101) Keep out of reach of children. (P102)

Prevention: Obtain special instructions before use. (P201)

Do not breathe vapour/mist. (P260)

Response: IF SWALLOWED: Immediately call a POISON

CENTER/doctor. (P301+P310)

Get medical advice/attention if you feel

unwell. (P314)

Storage: Store locked up. (P405)

Disposal: Dispose of contents/container in accordance

with local regulation. (P501)

Hazardous substances: toluene

Additional labelling: Not applicable.

2.3. Other hazards

Additional warnings: This mixture/product does not contain any

substances considered to meet the criteria classifying them as PBT and/or vPvB. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU)

2018/605.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Product/substance	Identifiers	% w/w	Classification	Note
toluene	CAS No.: 108-88-3	95-100%	Flam. Liq. 2, H225	[1],
	EC No.: 203-625-9		Asp. Tox. 1, H304	[3]
	UK-REACH:		Skin Irrit. 2, H315	
	Index No.: 601-021-00-3		STOT SE 3, H336	
			Repr. 2, H361	
			STOT RE 2, H373	

3.2. Mixtures

Not applicable. This product is a substance.

Toluene 99.9 +%, extra pure Page 2 of 12



See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

- [1] European occupational exposure limit.
- [3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information: In the case of accident: Contact a doctor or

casualty department – take the label or this

safety data sheet.

Contact a doctor if in doubt about the injured person's condition or if the symptoms persist.

Never give an unconscious person water or

other drink.

Inhalation: Upon breathing difficulties or irritation of the

respiratory tract: Bring the person into fresh

air and stay with him/her.

Skin contact: Remove contaminated clothing and shoes

immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents

or thinners.

If skin irritation occurs: Get medical

advice/attention.

Eye contact: Upon irritation of the eye: Remove contact

lenses and open eyes widely. Flush eyes with water or saline water (20-30 °C) for at least 5 minutes. Seek medical assistance and

continue flushing during transport.

Ingestion: IF SWALLOWED: Immediately call a POISON

CENTER/doctor.

Do not induce vomiting! If vomiting occurs, keep head facing down so that vomit does not get into the lungs. Call a doctor or ambulance. Symptoms of chemical

pneumonia can appear after several hours. People who have swallowed the product should therefore be kept under medical

attention for at least 48 hours.

Burns: Rinse with water until pain stops then

continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

This product contains substances that can cause chemical pneumonia if swallowed. Symptoms of chemical pneumonia may appear after several hours.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in

Toluene 99.9 +%, extra pure Page 3 of 12



concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed IF exposed or concerned:

Get immediate medical advice/attention.

det illillediate medical advice/attention

Information to medics:

Bring this safety data sheet or the label from this product.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist. Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters. If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO2)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: 3YE

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: HANDLING AND STORAGE

Toluene 99.9 +%, extra pure Page 4 of 12

7.1. Precautions for safe handling

Ground and bond container and receiving equipment.

Use explosion-proof [electrical/lighting/ventilating] equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Avoid direct contact with the product.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Take action to prevent static discharges.

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material: Keep only in original packaging. Storage temperature: Room temperature 15 to 25°C

Incompatible materials: Strong oxidizing agents

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

toluene

No substances are listed in the national list of substances with an occupational exposure limit.

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

Control is unnecessary if the product is used as intended.

General recommendations: Smoking, drinking and consumption of food

is not allowed in the work area.

Exposure scenarios: There are no exposure scenarios

implemented for this product.

Exposure limits: Occupational exposure limits have not been

defined for the substances in this product.

Appropriate technical measures: Do not recirculate outlet air that contain the

substances.

Hygiene measures: Take off contaminated clothing and wash it

before reuse.

Measures to avoid environmental exposure: Keep damming materials near the workplace.

If possible, collect spillage during work.

8.3. Individual protection measures, such as personal protective equipment

Generally: Use only UKCA marked protective equipment.

Respiratory Equipment:



Туре	Class	Colour	Standards	
А	Class 1 (low capacity)	Brown	EN14387	(B)

Skin protection:

Recommended	Type/Category	Standards	
Dedicated work clothing should be worn.	-	-	

Hand protection:

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	0,2	> 480	EN374-2, EN374-3, EN388	

Eye protection:

Туре	Standards	
Safety glasses with side shields.	EN166	

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state: Liquid

Colour: Transparent
Odour / Odour threshold: Aromatic

pH: Testing not relevant or not possible due to

the nature of the product.

Density (g/cm^3) : 0.87

Kinematic viscosity: Testing not relevant or not possible due to

the nature of the product.

Particle characteristics: Does not apply to liquids.

Phase changes

Melting point/Freezing point (°C): -95

Softening point/range (waxes and pastes) (°C): Does not apply to liquids.

Boiling point (°C): 110.6

Vapour pressure: 29 hPa (20 °C)

Relative vapour density: 3,18

Decomposition temperature (°C): Testing not relevant or not possible due to

the nature of the product.

Data on fire and explosion hazards

Toluene 99.9 +%, extra pure Page 6 of 12



Flash point (°C): 4.4

Flammability (°C): The material is ignitiable.

Auto-ignition temperature (°C): 480

Lower and upper explosion limit (% v/v): Testing not relevant or not possible due to

the nature of the product.

Solubility

Solubility in water: Testing not relevant or not possible due to

the nature of the product.

n-octanol/water coefficient: Testing not relevant or not possible due to

the nature of the product.

Solubility in fat (g/L): Testing not relevant or not possible due to

the nature of the product.

9.2. Other information

Other physical and chemical parameters: No data available.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Toluene 99.9 +%, extra pure Page 7 of 12



Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards

Long term effects

Reproductive toxicity: This product contains teratogenic substances, which may produce anomalies and/or developmental defects to the human offspring. Adverse effects include: death, growth retardation, congenital disorders, delayed mental development, and functional disorders. This product contains reprotoxic substances, which may harm the reproductive capacity. Adverse effects include: sterility, effects on the sexual function, lowered effective fertility and dysfunctional menstrual cycle.

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

Not applicable.

Other information

toluene has been classified by IARC as a group 3 carcinogen.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No data available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria



classifying them as PBT and/or vPvB.

12.6. Endocrine disrupting properties

Not applicable.

12.7. Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 5 - Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

HP 10 - Toxic for reproduction

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law

EWC code

Not applicable.

Specific labelling

Not applicable.

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: TRANSPORT INFORMATION

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1294	TOLUENE	Class: 3 Labels: 3 Classification code: F1	II	No	Limited quantities: 1 L Tunnel restriction code: (D/E) See below for additional information.
IMDG	UN1294	TOLUENE	Class: 3 Labels: 3 Classification code: F1	II	No	Limited quantities: 1 L EmS: F-E S-D See below for additional information.
IATA	UN1294	TOLUENE	Class: 3 Labels: 3 Classification code: F1	II	No	See below for additional information.

Toluene 99.9 +%, extra pure Page 9 of 12



14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	Other information:
		3		

^{*} Packing group

Additional information

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: 3YE

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application: People under the age of 18 shall not be

exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate

exposure, must be considered.

Demands for specific education:

No specific requirements.

SEVESO - Categories / dangerous substances: P5c - FLAMMABLE LIQUIDS, Qualifying

quantity (lower-tier): 5.000 tonnes / (upper-

tier): 50.000 tonnes

Regulation on drug precursors: toluene is included (Category 3)

UK-REACH, Annex XVII

toluene is subject to restrictions, UK-REACH annex XVII (entry 48).

Additional information: Tactile warning.

If this product is sold in retail, it must be delivered with child-resistant fastening.

Sources: The Management of Health and Safety at

Work Regulations 1999.

The Health and Safety at Work etc. Act 1974

Regulations 2013.

Toluene 99.9 +%, extra pure Page 10 of 12

^{**} Environmental hazards

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18

December 2014 on waste as retained and amended in UK law.

The Controlled Drugs (Drug Precursors)

Regulations 2008.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained

and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: OTHER INFORMATION

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H336, May cause drowsiness or dizziness.

H361, Suspected of damaging fertility or the unborn child.

H373, May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as



modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

Chris

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en

Toluene 99.9 +%, extra pure